



## DOME TYPE SCM SPLICE CLOSURE CAN-DO-8001-024

- IP68
- Total 7 inlet/outlet ports
- 6 round ports (each port for 8 drop cable with maximum diameter up to 6 mm)
- Diameter of oval port is 30 mm
- Single circuit management (SCM) cassette
- Closure construction and lightweight plastic provides strength and resistance to chemical and U.V attack
- All installation accessories are included, good sealed performance.
- Sheath retention & central strength member fastening system included.
- Quick installation type, easy to install and maintain.

### Technical Details

<b>Dimensions</b>	700 mm x 285 mm (H x D)
<b>Material</b>	Polypropylene
<b>Weight</b>	4,5 kg
<b>Maximum Port Capacity</b>	Up to 1344 fibers

### Application

Underground, Aerial, Vault, Pole Mounting.

### Drop Cable Sealing Kits for Round Port

- Only applicable for 6 round port option
- Round port closing kit BC6-002-M8-6 mm
- Round Port Ø 30 mm
- Up to 8 drop cables
- Maximum diameter of cables Ø 6 mm

### Accessories

- Earthing kit
- Buffer tube for bunchy and ribbon fiber
- Pressure testing valve
- Branching clip
- Heat shrinkable fixing sleeve
- Metal hoop

